

# MPC KIT

MULTI-PURPOSE COMBO KIT

ANY BRAND  
**TRADE-IN**  
ANY CONDITION

## Pipe & Cable **AND** Magnetic Locating



XTpc



GA-92XTd



### #1 Choice for Utilities Locating

Water • Sewer • Gas • Electric • Telecomm

CABLE TV LINES • CAST OR DUCTILE IRON PIPES  
COPPER PIPE • CORNER MARKERS • CURB & VALVE BOXES  
ENCLOSURES • FIBER OPTIC W/ TRACER OR SHIELD  
GAS LINES • HAZMAT DRUMS • IRRIGATION LINES  
MAG & PK NAILS • MANHOLE COVERS • MARKER MAGNETS  
PLASTIC PIPE W/ TRACER WIRE • POWER LINES  
SEPTIC TANKS • STEEL PIPES • STREET LIGHT POWER  
TELEPHONE LINES • WATER & SEWER LINES • WELL CASINGS



World of SCHONSTEDT



**SCHONSTEDT**   
INSTRUMENT COMPANY  
*Making Locating Easier Since 1953*

**SCHONSTEDT**  
MADE IN USA

100% EMPLOYEE-OWNED COMPANY

[www.schonstedt.com](http://www.schonstedt.com)

# MPCKIT MULTI-PURPOSE COMBO KIT

## MPCKIT includes

- **GA-92XTd Magnetic Locator**
- **XTpc Pipe & Cable Locator**
- Inductive Antenna • Transmitter • Holster Clip • Ground Stake
- Power Supply & Charger for XTpc (AC/DC)
- Conductive Clips Assembly • Small Heavy Duty Conductive Clip
- Instruction Manual for XTpc & GA-92XTd
- Rugged carrying hard case with custom foam insert

### Available in 3 models:

**MPC-800:** Includes an XTpc-82 Pipe & Cable Locator and a GA-92XTd Magnetic Locator

**MPC-300:** Includes an XTpc-33 Pipe & Cable Locator and a GA-92XTd Magnetic Locator

**MPC-500:** (not pictured) Includes an XT-512 Camera & Sonde Locator and a GA-92XTd Magnetic Locator



### GA-92XTd Specifications

<b>Output</b>	<b>Audio:</b> Signal increases or decreases in frequency with signal strength (gradient field intensity). Audio frequency range - 30 to 4000 Hz. <b>Visual:</b> Expanding bar-graphs indicate polarity (positive or negative) and signal strength. Digital readout shows gradient field intensity expressed in milligauss (mG). Range - 0 to 500 mG
<b>Battery Indicator</b>	4-segment LCD
<b>Gain</b>	4-Level LCD - Low (L), Medium (M), High (H), Extra High (XH)
<b>Volume</b>	3 Levels, Muted, Medium and Maximum
<b>Input Power</b>	One 9V battery (Lithium recommended, but not required)
<b>Battery Life</b>	24 Hours (intermittent usage)
<b>Operating Temperature</b>	-13° F to 140° F (-25° C to 60° C)
<b>Water resistant Length</b>	11.5" (29 cm), only when operated in open position
<b>Overall Length</b>	Open - 26" (66 cm), Closed - 15.5" (39 cm)
<b>Nominal Sensor Spacing</b>	9.5" (24 cm)
<b>Weight</b>	2.4 lb (1.1 Kg)
<b>Construction Material</b>	High impact ABS

### XTpc Receiver Specifications

<b>Operating Frequency</b>	82kHz or 33kHz plus 50/60Hz passive detection (factory selectable)
<b>Battery</b>	9 V single battery
<b>Battery Life</b>	18 hrs intermittent use
<b>LCD Display</b>	3 1/2 digit reflective Signal Strength, Directional Arrows, Battery Status, Volume and Depth
<b>Controls</b>	ON/Volume adjustment, OFF, DEPTH, SONDE, AUTO GAIN, UP gain, DOWN gain, PASSIVE
<b>Dimensions</b>	Unit extended: 26 in (~66 cm) Unit collapsed: 15.5 in (~39 cm)
<b>Weight</b>	Under 2.5 Lbs

### XTpc Transmitter Specifications

<b>Operating Frequency</b>	82kHz or 33kHz (factory selectable)
<b>Dimensions</b>	7.2" L x 2.2" W x 1.5" H
<b>Battery Type</b>	Rechargeable NiMH 7.2 V, 3800mAh
<b>Battery Life</b>	8 hours continuous use
<b>Output Power</b>	Maximum 1-watt allowed under FCC at 82kHz; 1.8-watt at 33kHz
<b>Controls</b>	ON/OFF UP Power DOWN Power
<b>LCD</b>	3 1/2 digit reflective Battery Status, Mode, Output Power Level, Output Current (mA)
<b>Weight</b>	Under 2 lbs

*\*Specifications subject to change without notice*

Order/Info Hotline:  
**800-999-8280**



Order/Info Online:  
**www.schonstedt.com**

**SCHONSTEDT**   
INSTRUMENT COMPANY

*Making Locating Easier Since 1953*

*an employee-owned company*